

AXIS Outdoor Vandal Fusion Dome

Weatherproof your AXIS 213 PTZ Network Camera

The AXIS Outdoor Vandal Fusion Dome housing protects the AXIS 213 PTZ Network Camera in outdoor environments, as well as indoor conditions that may be humid, cold or dusty. The housing provides NEMA 4X for water ingress and up to IP66 class protection from dust and water ingress. With a heater and a blower, the housing enables the camera to operate in temperatures ranging from -6°F to 105°F (-20°C to $+40^{\circ}\text{C}$).

The housing ships with a smoked dome, which allows for discreet surveillance. Its lower semi-sphere is constructed of .11" polycarbonate. The housing ships with a wall-mounting bracket that can be replaced with a variety of mounting options, all of which provide protective passage for all necessary cabling.



- Indoor and outdoor installation
- Vandal resistant cast aluminum construction
- Operating temperature:
 -6°F to 105°F (-20°C to $+40^{\circ}\text{C}$)
- Tailor-made for the AXIS 213
- A variety of mounting options available

AXIS Outdoor Vandal Fusion Dome

Technical Data – dome housing

General

- Constructed of vandal resistant cast aluminum top, 94VO, with UV protected polycarbonate lower dome
- Optically clear .118" thick tinted lower dome
- Power supply included with kit

Environment

- Indoor or outdoor
- NEMA 4X for water ingress and up to IP66
- 24 hour fan operation for effective heating and condensation protection
- Thermostatically control 24VAC heater
- Operating temperature:
-6 F to 105 F (-20°C to +40°C)

Electrical

- Input voltage 110-120 60HZ VAC
- Input current Max 0.9A

Dimensions and Weight

- Product dimensions (H x W x L):
13.3 x 9.8 x 14.6 inches
(340 x 250 x 370 mm)
- Shipping dimensions (H x W x L):
17 x 14 x 17 inches
(432 x 356 x 432 mm)
- Unit Weight: 14.0 lbs (6.4 kg)
- Shipping Weight: 18.0 lbs (8.2 kg)

Approvals

Safety: All included electrical components are UL approved

Available Accessories

Optional mounting accessories (see table below)

Technical Data – mounts

To receive a fully working unit for outdoor or indoor use, please use the following guide and select those accessories that meet the requirements of your installation.

1	2
<p>AXIS 213 PTZ Network Camera</p> 	<p>Optional Accessory 21896 Pole Mount*</p>  <p>* Banding tool is required for mounting the 21896 Pole Mount accessory</p> <p>Optional Accessory 22059 Corner Mount</p> 

www.axis.com